



GW4

STANDARD WALKWAY WITH SINGLE GUARDRAIL

Fixed aluminium walkway with guardrail on one side for fall protection. The KATT fixed walkway systems are best-in-class permanent walkways ensuring clear demarcation routes for personnel on roof top.

KEY FEATURES

Modular fixed design

Pace comprises modular high quality, aluminium components to create a strong, durable walkway that's easy to install.

Ease of installation

Our systems are simple and quick to install.

Safe and secure

Compliant with the relevant technical standards.

Adaptable

KATT Walkway systems are tailored to meet your exact requirements.

Compliant with standards

BS EN ISO 14122-3:2016 /
BS 4592 & BS EN 516



BENEFITS OF PACE WALKWAY SYSTEMS

- Sturdy, heavy duty aluminium construction - Low maintenance
- Provides a controlled access pathway for workers on roofs
- Fixes to standing seam roofs or to R panel roof systems
- Can be mounted on membrane and built-up roof systems

We provide you with access solutions guaranteed to make your work easier.





SPECIFICATIONS

Materials	<ul style="list-style-type: none"> Walkway – mill finish, expanded aluminium grating Roof battens – mill finish profiled aluminium
Dimensions	<ul style="list-style-type: none"> Walkway grating length – 3000mm/6000mm Walkway grating width – 600mm mounted 450mm below handrail Walkway grating thickness – 13mm Support batten – 700mm(L) x 40mm(H)
Characteristics	<ul style="list-style-type: none"> Modular Design High Strength Aluminium construction Lightweight components Multi-directional, non-slip walkway surface Non-corrosive materials provide maintenance free protection
Quality assurance	All KATT Walk components are manufactured by our ISO-9001 certified partners. KATT Safety recognises the importance of all products being consistent in quality and regularly inspects the production process to ensure best quality products are produced.
Weight	<ul style="list-style-type: none"> 4.5 kg per linear metre (6.4kg per m2) Roof battens – mill finish profiled aluminium
Working load limit	<ul style="list-style-type: none"> 4.8 kPA (500mm span / 2.5mm max deflection) 2.5 kPA (670mm span / 3.2mm max deflection) 1.8 kPA (700mm span / 3.5mm max deflection)
Compliance	<ul style="list-style-type: none"> KATT Walkway Systems are designed and tested to comply with requirements of BS EN ISO 14122- 3:2016 and relevant statutory HSE guidelines Walkway surface has been tested and complies with BS EN 516:2006
Product warranty	10 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations.

FURTHER INFORMATION

Inspection and maintenance

Visual inspection for any damage or loose fixings must be done periodically and prior to use. Basic wear and tear preventative maintenance is recommended, as per manufacturer's specifications and recommendations.

Important note

Failure to supply and/or install proprietary product in accordance with above specifications and installation / usage guidelines voids complete system certification and/or warranty.



Protecting life by providing permanent
Safe Access Systems

0800 0590 400

kattsafety.co.uk

KATT
SAFETY
PART OF **MCDSAFE**