



RL72

MODULAR STEPPED LADDER WITH 400MM PLATFORM

A modular stepped ladder with grabrails and 400mm landing designed to attach to front face of structure or platform. The perfect ladder for fitting to the underside of a roof hatch. The ladder is formed with steps rather than rungs making this ladder type more comfortable for user. The KATT modular step ladders provide an easy climb for accessing areas at height where space is not a limitation. All step ladders are installed to 65° angle.

KEY FEATURES

Welded aluminium construction

Providing sturdy, secure, and reliable access.

Lightweight

Enabling simple and quick installation, saving you and your employees time and effort.

Modular system

Ensures easy assembly & delivery.

Cost effective

Non-corrosive and maintenance free.

Safe and easy to use

Providing you with peace of mind that your employees are protected.

Compliant with standards

BS4211:2005 & BS EN ISO 14122-4:2016



APPLICATIONS

- Access to roof hatches
- Access to mezzanines
- Access to varying roof heights
- Safe access over roof mounted machinery and dangerous zones

We provide you with access solutions guaranteed to make your work easier.





KITS

Ladder exit type	Ladder with grabrails
Height up to 1000mm	RL70.SL40.0100
Height up to 2000mm	RL70.SL40.0200
Height up to 3000mm	RL70.SL40.0300
Compliance	All KATT® Ladder Systems are designed to comply with requirements of BS4211:2005 & BS EN ISO 14122-4:2016 and relevant statutory HSE guidelines.
Working load limit	<input type="checkbox"/> Recommended for single person use – 150kg rated <input type="checkbox"/> Industrial rated, suited to high frequency usage

- These ladders are modular
- Over-length ladders are trimmed to suit site conditions
- Heights stated are measured to the exit point
- ISO 14122-4 states that a single flight ladder >3,000mm and <10,000mm shall be equipped with a safety cage or fall arrester

For assistance with product selection or for advice on requirements for a specific project please contact KATT Safety.

LADDER MOUNTING OPTIONS

We offer 3 types of mounts for full stability of your fixed access ladder.

1. Standard floor mounts
2. Non-penetrating base plates
3. Off-floor mounted fixing brackets

Neither option will penetrate the roofing substrate, and the off-floor bracket keeps the ladder off the roof entirely, affixing it to the wall instead.

FURTHER INFORMATION

Each ladder is provided with all necessary fasteners and attachment hardware. By cutting the lower ladder body to the required length, the system can be built to suit exact site requirements.

Often, prefabricated ladders are delivered to site and the critical dimensions, or the spacing of fixing brackets, are incorrect. This results in additional costs and time delays whilst the fabrication is adjusted.

With the modular KATT® Ladder System, you simply build the kit to suit the site layout.

Protecting life by providing permanent
Safe Access Systems

0800 0590 400

kattsafety.co.uk

